



BLCA10X1

Blast Chiller/Freezer GN1/1

Product Features

- Touch screen controller
- Programmable thermostat
- HACCP compliant data export
- Upload or download data via USB
- Guides for GN1/1 and Euronorm pans
- Stainless steel
- Core sensor included
- Reversible self-closing door
- Adjustable legs
- (Chill +70°C to +3°C) 40kg in 90 mins
- (Freeze +70°C to -18°C) 28kg in 240 mins

Blast chiller/freezer with touch screen controller

Our blast chiller/freezer range is perfect for quickly cooling or freezing hot food from the stove or oven, preserving the food in a safe way. The BLCA-X comes with an easy-to-use touch screen controller. Here you can choose one of the pre-set programs for different purposes or you can create and save your own programs. The unit comes with pre-set special cycles for fish, hardening of ice cream, drying as well as for defrosting. It is possible to upload your own recipes or download data for HACCP purposes via an USB port. Primary programs are pre-set to keep the end temperature fixed until the cabinet is opened and the program is turned off. This method ensures the quality and safe preservation of the food and makes sure the food is safe for storage and later consumption. Cooling capacity is measured from +70 to +3 °C in 90 minutes - Freezing capacity is measured from +70 to -18 °C in 240 minutes. Exact kg capacity for each model can be found under the technical specifications. The BLCA-X accepts both gastronorm 1/1 and euronorm pans (not included).

Measures and Content

Capacity Cooling	kg	40
Capacity Freezing	kg	28
Capacity GN Pans	pcs	10
Temperature Range	°C	-30 to +70
Climate Class		5
Gross / Net Weight	kg	190 / 150
Gross Volume	l	368
Gross / Net Volume	l	368 / 192

Design and Material

Door No & Type	1 hinged self-closing solid door	
Door Reversible	Yes	
Feet / Legs	4 adjustable feet	
Exterior Finish	SS304	
Interior Finish	SS304	
Interior Light	No	
Lock	No	

Cooling and Functions

Type of Controller	Programmable Touchscreen	
Type of Cooling	Blast	
Type of Defrost	Automatic, hot gas	
Refrigerant	R290	
Refrigerant Charge	g	165

Power and Consumption

Input Power	W	900
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions

Internal Dimension (WxDxH)	mm	660 x 640 x 870
External Dimension (WxDxH)	mm	804 x 815 x 1885
Packed Dimension (WxDxH)	mm	870 x 900 x 1730
40ft Container Load	pcs	26



Core sensor included



Touch screen controller